

PRODUCT INFORMATION

- Insert coat made of boiler steel, with thickness of 3 mm, P265GH grade in accordance with EN 10028-2
- Steel doors made of special profile, guaranteeing rigidity and high-temperature resistance.
- Heat-resistant ceramic glass with working temperatures of up to 800 °C.
- Steel base of insert fitted with an intake throttle of outside cold air.
- Insert equipped with air curtain, to guarantee the maintenance of a substantially pure glass effect.
- Specially designed rear part of the body, designed for secondary air supply to the upper part of the furnace. Allows to increase the efficiency of the device by after-burning the exhaust fumes.

RIGHT-SIDED HORIZONTAL FIREPLACE INSERT **ALBERO AL19R.H**

Nominal power (kW)

19

Heating load range (kW)

9-23

Flue diameter (mm)

220

Heat performance (%)

81,6

CO emission (with 13% O₂)

0,088

Dust emission (g/m³)

0,039

Exhaust emission (°C)

314

Weight (kg)

201

Log maximum length (cm)

70

Material

boiler steel with thickness of 3 mm P265GH

Fuel Type

hardwood, briquettes, lignite

Min. Active field of exhaust grilles (cm²)

1000

Min. Active field of intake grilles (cm²)

800

Size of fireplace glass (mm)

900 x 415 x 375

